

# Certificate of Technical Specifications



PRODUCT: FILETADO  
FORMAT: 437x631x10,3 mm

CONTAINS: 6 Pieces 1,65m² 17,76 SQFT

GROUP: B1b

| Technical Characteristics                        | ISO       | Req.             | Unit  | Specification |
|--------------------------------------------------|-----------|------------------|-------|---------------|
| DIM. VAR. IN REL. W. OF THE GREATER SIDE         | 10545-2   | ±1,0             | mm    | ±0.50         |
| DIM. VAR. IN REL. W. OF THE MINOR SIDE           | 10545-2   | ±1,0             | mm    | ±0.50         |
| THICKNESS VARIATION                              | 10545-2   | ±0,50            | mm    | ±0.50         |
| STRAIGHTNESS OF THE GREATER SIDE                 | 10545-2   | ±0,80            | mm    | ±0.80         |
| STRAIGHTNESS OF THE MINOR SIDE                   | 10545-2   | ±0,80            | mm    | ±0.80         |
| DEVIATION FROM ORTHOGONALITY OF THE GREATER SIDE | 10545-2   | ±1,50            | mm    | ±1.50         |
| DEVIATION FROM ORTHOGONALITY OF THE MINOR SIDE   | 10545-2   | ±1,35            | mm    | ±1.35         |
| CENTRAL DIAGONAL CURVATURE DEVIATION             | 10545-2   | ±1,80            | mm    | ±1.80         |
| DEVIATION OF THE CURVATURE OF THE SIDES          | 10545-2   | ±1,80            | mm    | ±1.80         |
| DEVIATION OF THE CURVATURE OF THE SIDES          | 10545-2   | ±1,35            | mm    | ±1.35         |
| BENDING OVER DIAGONAL                            | 10545-2   | ±1,8             | mm    | ±1.8          |
| QUALITY OF SURFACE                               | 10545-2   | ≥95              | %     | ≥95           |
| WATER ABSORPTION                                 | 10545-3   | 6 a 10           | %     | 6 a 10        |
| RESISTANCE TO BENDING                            | 10545-4   | ≥18              | N/mm2 | ≥18           |
| BREAKING STRENGTH                                | 10545-4   | ≥800             | N     | ≥800          |
| CLASS OF USAGE                                   | -         | -                | USE:  | 2             |
| THERMAL SHOCK RESISTANCE                         | 10545-9   | -                | -     | -             |
| LINEAR EXPANSION COEFFICIENT X 10-6              | 10545-8   | -                | C-1   | -             |
| MOISTURE EXPANSION                               | 10545-10  | -                | mm/m  | ≤0.30         |
| GRAZING RESISTANCE                               | 10545-11  | Required         | -     | OK            |
| RESISTANCE TO CHEMICALS                          | 10545-13  | Minimum Class GB | -     | GA            |
| RESISTANCE ATTACKS ACID/ALKALINE                 | 10545-13  | Specify          | -     | GLB           |
| SURFACE RESISTANCE TO STAINS                     | 10545-14  | Minimum Class 3  | -     | 5             |
| COEFFICIENT OF FRICTION WET                      | NBR 16919 | Specify          |       | -             |
| CHANGES IN HUE                                   |           |                  |       | V2            |

Note: Product in accordance with the ABNT NBR 13006 standard  
Evaluation of reaction to fire (NBR15575): Class I (non-combustible)  
USE 2- Use on internal and external walls.

  
Jamilson Pinter Júnior  
Responsável Técnico RC1 e RC2

  
Gildino da Luz  
Responsável Técnico RC3 e RC4